












PolarP™ P-Channel Power MOSFETs



Part Type	V _{DSS}	I _{D(cont)} T _C = 25°C	R _{DS(on)} T _J = 25°C	C _{iss} typ.	Q _g typ.	t _{rr} typ.	R _{thJC}	P _D	Fig. No.	Package style Outline drawings on pages O-30...O-52	
➤ New	V	A	Ω	pF	nC	ns	K/W	W			
IXTA 52P10P	-100	-52.0	0.050	2845	60	120	0.42	300	X011b	TO-220AB X005a Weight = 4 g  X014a X005a X017a X014a X019	
IXTH 52P10P		-52.0	0.050	2845	60	120	0.42	300	X014a		
IXTP 52P10P		-52.0	0.050	2845	60	120	0.42	300	X005a		
IXTQ 52P10P		-52.0	0.050	2845	60	120	0.42	300	X017a		
IXTH 90P10P		-90.0	In Development								X014a
IXTT 90P10P		-90.0	In Development								X019
IXTK 170P10P		* -170.0	0.012	1260	240	176	0.14	890	X020a		TO-263AB X011b Weight = 2 g  X027a X015a
IXTN 170P10P		* -170.0	0.012	1260	240	176	0.14	890	X027a		
IXTX 170P10P		* -170.0	0.012	1260	240	176	0.14	890	X015a		
IXTA 36P15P	-150	-36.0	0.110	3100	55	228	0.42	300	X011b	TO-247AD X014a Weight = 6 g  X005a X017a	
IXTP 36P15P		-36.0	0.110	3100	55	228	0.42	300	X005a		
IXTQ 36P15P		-36.0	0.110	3100	55	228	0.42	300	X017a		
IXTA 26P20P	-200	-26.0	0.170	2740	56	240	0.42	300	X011b	TO-247AD X014a Weight = 6 g  X014a X005a X017a X014a X019 PLUS247 X015a Weight = 5 g  X020a X027a X016a X015a	
IXTH 26P20P		-26.0	0.170	2740	56	240	0.42	300	X014a		
IXTP 26P20P		-26.0	0.170	2740	56	240	0.42	300	X005a		
IXTQ 26P20P		-26.0	0.170	2740	56	240	0.42	300	X017a		
IXTH 48P20P		-48.0	In Development								X014a
IXTT 48P20P		-48.0	In Development								X019
IXTK 90P20P		-90.0	0.044	12000	205	315	0.14	890	X020a		
IXTN 90P20P		-90.0	0.044	12000	205	315	0.14	890	X027a		
IXTR 90P20P		-53.0	0.048	12000	205	315	0.40	312	X016a		
IXTX 90P20P		-90.0	0.044	12000	205	315	0.14	890	X015a		
IXTA 10P50P	-500	-10.0	1.000	2670	50	414	0.50	250	X011b	ISOPLUS247™ X016a Weight = 5 g  X014a X005a X017a X014a X019 X017a TO-3P X027a Weight = 5 g  X016a X015a	
IXTH 10P50P		-10.0	1.000	2670	50	414	0.50	250	X014a		
IXTP 10P50P		-10.0	1.000	2670	50	414	0.50	250	X005a		
IXTQ 10P50P		-10.0	1.000	2670	50	414	0.50	250	X017a		
IXTH 20P50P		-20.0	In Development								X014a
IXTT 20P50P		-20.0	In Development								X019
IXTK 40P50P		-40.0	0.230	11500	205	477	0.14	890	X020a		
IXTN 40P50P		-40.0	0.230	11500	205	477	0.14	890	X027a		
IXTR 40P50P		-22.0	0.260	11500	205	477	0.40	312	X016a		
IXTX 40P50P		-40.0	0.230	11500	205	477	0.14	890	X015a		
IXTH 16P60P	-600	-16.0	In Development							X014a	TO-268AA X019 Weight = 5 g  X019 X020a X027a X015a
IXTT 16P60P		-16.0	In Development							X019	
IXTK 32P60P		-32.0	In Development							X020a	
IXTN 32P60P		-32.0	In Development							X027a	
IXTX 32P60P		-32.0	In Development							X015a	
			In Development								

* limited by leads

TrenchP™ P-Channel Power MOSFETs

Part Number	V _{DSS}	I _D T _C = 25°C	R _{DS(on)} T _C = 25°C	C _{iss} typ.	Q _G typ.	t _{rr} typ.	R _{thJC}	P _D	Fig. No.	Package style Outline drawings on pages O-30...O-52
➤ New	V	A	mΩ	pF	nC	nS	K/W	W		
IXTA 32P05T	-50	32	36	1975	46	26	1.5	83	X011b	SOT-227B miniBLOC X027a Weight = 30 g  X005a
IXTP 32P05T		32	36	1975	46	26	1.5	83	X005a	
IXTA 28P065T	-65	28	45	2030	46	31	1.5	83	X011b	 X005a X011b X005a X011b X005a X011b
IXTP 28P065T		28	45	2030	46	31	1.5	83	X005a	
IXTA 24P085T	-85	24	65	2090	41	40	1.5	83	X011b	
IXTP 24P085T		24	65	2090	41	40	1.5	83	X005a	
IXTA 18P10T	-100	18	120	2100	39	62	1.5	83	X011b	
IXTP 18P10T		18	120	2100	39	62	1.5	83	X005a	